



## China 608zz Bearing Supplier



6315 C3- O&Kai Z1V1 Z2V2 Z3V3 ISO Deep Groove Ball Bearing SKF NSK NTN NACHI Koyo FAG OEM

Bearing No. 6315

6315 Bearing 2D drawings and 3D CAD models

Size	75x160x37 mm
Bore Diameter	75 mm
Outer Diameter	160 mm
Width	37 mm
d	75 mm
D	160 mm
B	37 mm
C	37 mm
r min.	2.1 mm
da min.	87 mm
Da max.	148 mm
ra max.	2.0 mm
Weight	3.02 Kg
Basic dynamic load rating (C)	113 kN
Basic static load rating (C0)	77 kN
(Grease) Lubrication Speed	4100 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0



## China 608zz Bearing Supplier

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	75MM Bore; 160MM Outside Diameter; 37MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nachiamerica.com">http://www.nachiamerica.com</a>
Outside Diameter	6.299 Inch   160 Millimeter
Bore	2.953 Inch   75 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	1.457 Inch   37 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	75 mm
Width	37 mm
Fillet Radius/Chamfer	2.1 mm
Dynamic Load Rating	113,000 N



## China 608zz Bearing Supplier

Static Load Rating	77,000 N
Limiting Speed - Grease	4,300 rpm
Limiting Speed - Oil	5,000 rpm
Factor fo	13.2
Radial Clearance	0.010 to 0.030 mm
da (min)	87 mm
Da (max)	148 mm
ra (max)	2 mm